

(19) World Intellectual Property Organization
International Bureau



(43) International Publication Date
7 March 2002 (07.03.2002)

PCT

(10) International Publication Number
WO 02/18280 A1

- (51) International Patent Classification⁷: C02F 5/10, C11D 17/00
- (21) International Application Number: PCT/GB01/03927
- (22) International Filing Date:
3 September 2001 (03.09.2001)
- (25) Filing Language: English
- (26) Publication Language: English
- (30) Priority Data:
0021585.5 1 September 2000 (01.09.2000) GB
0023056.5 20 September 2000 (20.09.2000) GB
0030365.1 13 December 2000 (13.12.2000) GB
- (71) Applicant (for all designated States except US):
RECKITT BENCKISER (UK) LIMITED [GB/GB];
103-105 Bath Road, Slough, Berkshire SL1 3UH (GB).
- (72) Inventors; and
- (75) Inventors/Applicants (for US only): **MCKECHNIE, Malcolm, Tom** [GB/GB]; Spring Rise, 12A North Road, Lund, Drifffield, East Yorkshire YO25 9TF (GB). **CORNELIUS, Gay, Joyce** [GB/GB]; 57 The Wolds, Cottingham, East Yorkshire HU16 5LQ (GB).
- (74) Agents: **BROWN, Andrew, Stephen** et al.; Reckitt Benckiser plc, Group Patents Dept., Dansom Lane, Hull HU8 7DS (GB).
- (81) Designated States (national): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NO, NZ, PH, PL, PT, RO, RU, SD, SE, SG, SI, SK, SL, TJ, TM, TR, TT, TZ, UA, UG, US, UZ, VN, YU, ZA, ZW.
- (84) Designated States (regional): ARIPO patent (GH, GM, KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, CH, CY, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE, TR), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).
- Published:**
— with international search report
— before the expiration of the time limit for amending the claims and to be republished in the event of receipt of amendments
- For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.

BEST AVAILABLE COPY

WO 02/18280 A1

(54) Title: CLEANING METHOD

(57) Abstract: A method of cleaning household articles entails contacting cleaning water with a container containing a substantially water-insoluble modifying agent able to bind calcium ions. The container is permeable to water and to calcium ions but retains the modifying agent. The container may be a bag, for example of textile or paper.

CLEANING METHOD

This invention relates to a method of cleaning using aqueous solutions. In certain aspects the invention
5 relates products useful in such methods.

It is well known that certain metal compounds, notably calcium compounds, have a significant effect on the properties of water. "Hard" water containing a
10 significant loading of soluble calcium and magnesium compounds form a scum with soap or detergent and may require a large amount of soap or detergent in order for a lather to form. Scale deposits can readily form from such water, for example on heating or pH change or evaporation.
15 These deposits can be encrustations, or watermarks left on evaporation of water droplets from, especially, a shiny surface.

There have been many proposals for the removal of
20 metal ions from aqueous solutions. In the industrial context proposals have included filter beds and polymeric filters for capturing heavy metal ions from an aqueous solution flowing within a passageway. Examples are given in EP-A-992238 and GB-A-20869564. In the domestic context
25 sequestrants can be added to an aqueous washing solution and these can capture metal ions, such as calcium ions. Examples of such sequestrants are given in EP-A-892040. However in a multi-step washing process, such as that carried out by a clothes washing machine, it can be a
30 problem that the sequestrant is discharged with waste water, at an intermediate stage of the process, and is not available for later stages. Furthermore the waste water, containing the sequestrant, may be regarded as

environmentally undesirable. Another example from a domestic context is water jugs having a filter cartridge through which water trickles from an upper chamber to a lower chamber. The cartridges typically contain an ion
5 exchange resin and activated charcoal. They are reasonably effective but many consumers decline to purchase such jugs, which are, of necessity, bulky and cumbersome.

10 There is a need for a product which can change the properties of a water sample, for example by binding metal ions present in water, at least calcium ions and preferably also other metal ions, in a convenient manner, preferably through the entire course of a procedure (for
15 example a washing process) and preferably in such a manner as to avoid or minimise undesirable sequestrant components in the treated water.

 In accordance with a first aspect of the present
20 invention there is provided a method of cleaning household articles, wherein cleaning water is contacted with a container having an enclosing wall and containing a substantially water-insoluble modifying agent able to bind calcium ions, the wall being permeable to the water and to
25 components dissolved therein but retaining the substantially water-insoluble modifying agent.

 By substantially water-insoluble modifying agent we mean a modifying agent, more than 50% wt, preferably at
30 least 70% wt, more preferably at least 85% wt and most preferably at least 95% wt, and optimally 100% wt, of which is retained in the container, when the container is

used under the most rigorous conditions for which it is intended.

A method of cleaning may be a method of ware washing
5 using a machine, for example a clothes washing machine or
a dishwashing machine; the household article accordingly
may be an item of kitchenware and tableware, for example
crockery, glassware and tableware, or a textile article
such as an item of clothes or bed linen or a towel. In
10 such a method the modifying agent may soften the washing
water, reduce or eliminate the formation of scum in the
water and reduce or eliminate the deposition of limescale,
and preferably other metal compounds, from the water.
Unlike the known sequestrants mentioned above, formulated
15 to be washed away before the rinse cycle, in the present
method the container is preferably present during the
rinse cycle; either only the rinse cycle, or preferably,
throughout the washing operation, including the rinse
cycle. In such methods a cleaning agent is delivered to
20 the machine by dissolution of a liquid or solid cleaning
concentrate loaded into the machine prior to the start of
the washing operation. Such concentrates include a
surfactant, for example an anionic surfactant, or a non-
ionic surfactant, or a cationic surfactant, or an
25 amphoteric surfactant, or any combination thereof. They
typically also include one or more builders, which
themselves act as sequestrants.

A suitable anionic surfactant used in such a method of
30 the invention is an anionic organic surfactant, which is
usually employed in a soluble salt form, preferably as an
alkali metal salt, especially as a sodium salt. Although
other types of anionic detergents may be utilized, such as

higher fatty acyl sarcosides, alkyl sulphosuccinates, alkyl ether sulphosuccinates, alkylamide sulphosuccinates, alkyl sulphosuccinates, alkyl sulphoacetates, alkyl phosphates, alkyl ether phosphates, acyl isothionates, N-acyl taurates
5 and acyl lactylates, or conventional "soaps" of fatty acids, the preferred anionic surfactants employed are those which are described as being of a sulphonate or sulphate type. These include linear higher alkylaryl sulphonates (for example alkylbenzene sulphonates), alkyl sulphates,
10 alkyl ether sulphates, alkylamidoether sulphates, alkylarylpolyether sulphates, monoglyceride sulphates, alkyl sulphonates, alkylamido sulphonates, higher fatty alcohol sulphates, higher fatty alcohol polyalkoxylate sulphates, olefin sulphonates, α -methyl ester sulphonates
15 and paraffin sulphonates. An extensive listing of anionic detergents, including such sulph(on)ate surfactants, is given at pages 25 to 138 of the text Surface Active Agents and Detergents, Vol. II, by Schwartz, Perry and Berch, published in 1958 by Interscience Publishers, Inc., and is
20 incorporated herein by reference. Usually the higher alkyl group of such anionic surfactants is of 8 to 24, especially 10 to 20 carbon atoms, preferably 12 to 18 carbon atoms, and the alkoxylate content of such anionic surfactants that are alkoxylated (preferably ethoxylated or ethoxylated/
25 propoxylated) is in the range of 1 to 4 alkoxy groups per mole.

One preferred class of anionic surfactants comprise the alkali metal (preferably sodium) alkyl sulphates,
30 preferably having linear C₁₂₋₁₈ alkyl groups.


Another preferred class of anionic surfactants comprise alkali metal (preferably sodium) alkylaryl sulphonates

(especially alkylbenzene sulphonates), preferably having linear C₁₀₋₁₃ alkyl groups.

A preferred non-ionic surfactant used in this method of the invention is a condensation product of a higher fatty alcohol or alkyl phenol with a lower alkylene oxide, such as ethylene oxide or a mixture of ethylene oxide and propylene oxide. In such non-ionic surfactants the higher fatty moiety will normally be of 7 to 16 carbon atoms and there will usually be present from 3 to 20, preferably 4 to 15 moles of alkylene oxide per mole of higher fatty alcohol.


Another class of non-ionic surfactants that could be used are sorbitan esters of fatty acids having from 10 to 24 carbon atoms, for example sorbitan mono-oleate.

Amphoteric surfactants which may be used include amphoteric betaine surfactant compounds having the following general formula:



wherein R is a hydrophobic group which is an alkyl group containing from 10 to 22 carbon atoms, preferably from 12 to 18 carbon atoms, an alkylaryl or arylalkyl group containing a similar number of carbon atoms with a benzene ring being treated as equivalent to about 2 carbon atoms, and similar structures interrupted by amido or either linkages; each R₁ is an alkyl group containing from 1 to 3 carbon atoms; and R₂ is an alkylene group containing from 1 to 6 carbon atoms.

Examples of cationic surfactants which may be used include quaternary ammonium compounds and salts thereof, including quaternary ammonium compounds which also have germicidal activity and which may be characterized by the general structural formula:




when at least one of R_1 , R_2 , R_3 and R_4 is a hydrophobic, aliphatic, aryl aliphatic or aliphatic aryl group containing from 6 to 26 carbon atoms, and the entire cationic portion of the molecule has a molecular weight of at least 165. The hydrophobic groups may be long-chain alkyl, long-chain alkoxy aryl, long-chain alkyl aryl, halogen-substituted long-chain alkyl aryl, long-chain alkyl phenoxy alkyl or aryl alkyl. The remaining groups on the nitrogen atoms, other than the hydrophobic radicals, are generally hydrocarbon groups usually containing a total of no more than 12 carbon atoms. The radicals R_1 , R_2 , R_3 and R_4 may be straight chain or may be branched, but are preferably straight chain, and may include one or more amide or ester linkages. The radical X may be any salt-forming anionic radical.

Examples of quaternary ammonium salts within the above description include the alkyl ammonium halides such

as cetyl trimethyl ammonium bromide, alkyl aryl ammonium halides such as octadecyl dimethyl benzyl ammonium bromide, and N-alkyl pyridinium halides such as N-cetyl pyridinium bromide. Other suitable types of quaternary ammonium salts include those in which the molecule contains either amide or ester linkages, such as octyl phenoxy ethoxy ethyl dimethyl benzyl ammonium chloride and N-laurylcocoaminoformylmethyl)-pyridinium chloride. Other effective types of quaternary ammonium compounds which are useful as germicides includes those in which the hydrophobic radical is characterized by a substituted aromatic nucleus as in the case of lauryloxyphenyltrimethyl ammonium chloride, cetylaminophenyltrimethyl ammonium methosulphate, dodecylphenyltrimethyl ammonium methosulphate, dodecylphenyltrimethyl ammonium chloride and chlorinated dodecylphenyltrimethyl ammonium chloride.

Preferred quaternary ammonium compounds which act as germicides and which are useful in the present invention include those which have the structural formula:



wherein R_2 and R_3 are the same or different $\text{C}_8\text{--C}_{12}$ alkyl, or R_2 is $\text{C}_{12}\text{--C}_{16}$ alkyl, $\text{C}_8\text{--C}_{18}$ alkylethoxy, $\text{C}_8\text{--C}_{18}$ alkyl-phenolethoxy and R_2 is benzyl, and X is a halide, for example chloride, bromide or iodide, or methosulphate.

The alkyl groups R_2 and R_3 may be straight chain or branched, but are preferably substantially linear.

In any cleaning method of the invention, a mixture of
5 two or more surfactants may be used. Other known
surfactants not particularly described above may also be
used. Such surfactants are described in McCutcheon's
Detergents and Emulsifiers, North American Edition, 1982;
Kirk-Othmer, Encyclopaedia of Chemical Technology, 3rd
10 Ed., Vol. 22, pp 346-387.

It is preferred that the cleaning agent used in a
machine washing method contains a builder. Suitable
builders include water soluble inorganic salt builders,
15 preferably sodium salts, such as sodium polyphosphates,
e.g. sodium tripolyphosphate and sodium pyrophosphate,
sodium carbonate, sodium bicarbonate, sodium
sesquicarbonate, sodium silicate, sodium disilicate, sodium
metasilicate and sodium borate. In addition to the water
20 soluble inorganic salts, water insoluble builders may also
be useful, including the ion exchanging zeolites, such as
Zeolite 4A. Organic builders may also be employed. Among
suitable organic builders are polyacetal carboxylates, as
described in US-B-4725455, and water soluble salts of lower
25 hydroxycarboxylic acids, such as sodium citrate and sodium
gluconate. However, a builder may not be necessary as the
container may fulfil the main requirement of a builder, in
removing calcium ions.

30 Alternatively a method of cleaning in accordance with
the invention may be a manual method, for example using a
hand-cloth or mop, and an open vessel, for example a
bucket or bowl. Thus, the cleaning method could be a

method of cleaning a hard surface, for example a window, a tiled surface, shower screen, dirty tableware and kitchenware, a sanitaryware article, for example a lavatory, wash basin or sink, a car (which we regard as a
5 "household article" within the terms of this invention) or a kitchen worktop.

In a manual method the household article could also be a textile article. This could be as described above and
10 could also be a carpet. The cleaning method for a carpet could be purely manual, or manual but assisted by an electrical cleaning device.

In manual methods the cleaning agent is preferably
15 dissolved in water prior to the start of cleaning. The cleaning agent may comprise a surfactant, for example an anionic surfactant and/or a non-ionic surfactant, as described above.

20 The compositions used in any cleaning method of the invention may optionally include one or more conventional additives known to be useful in cleaning compositions including viscosity modification agents, fragrances (natural or synthetically produced), foaming or foam-
25 control agents, solvents, fillers, scale inhibitors, colouring agents, bleaching agents, and, particularly in the case of compositions for fabric washing, anti-nucleating agents, fabric conditioning agents, enzymes, hydrotropes and dye anti-redeposition agents. A germicidal
30 agent may be incorporated as an optional ingredient into the cleaning agents used in the invention. Examples are phenolic group containing compounds such as o-phenyl-phenol, o-benzyl[p-chlorophenol] and 4-tert-amylphenol.

However, as noted above, cationic surfactants mentioned above themselves have germicidal properties.

A container containing a sequestrant may act as a
5 water softener, promoting improved cleaning, within a vessel containing water, for example a bucket, jug, sink, toilet cistern or ware-washing machine. By capturing calcium ions, any cleaning agent present in the water can work more effectively, and/or the vessel is soiled or
10 scaled less, whether by soap scum or by encrustations or by watermarks ("spotting") left when droplets on a surface evaporate. For example the container may be used in the water used for cleaning windows or for washing a car, to soften the wash water and reduce "spotting".

15

A container containing a sequestrant may be disposed in a clothes washing machine throughout the wash and rinse cycles, for example by being placed in the machine's drum with laundry to be washed. Alternatively a container
20 containing a sequestrant may be disposed in the rinse portion of the loading drawer of a clothes washing machine, such that rinse water flowing through the loading drawer and into the machine is rendered lower in calcium ion concentration.

25

A sequestrant, serving as a calcium-binding modifying agent, could comprise polymeric bodies, for example of ion exchange resin. Suitable forms include beads and fibres. Examples include polyacrylic acid and algins. A
30 sequestrant could alternatively be an inorganic material, for example a granular zeolite which is retained by the container.

Algins may be found in and isolated from various organisms, in particular from algae belonging to the order *Phaeophyceae* and soil bacteria such as *Azotobacter vinelandii* and *Azotobacter crococcum* and from several strains of *Pseudomonas* bacteria. Common algal sources of algins include *Laminaria digitata*, *Ecklonia maxima*, *Macrocystis pyrifera*, *Lessonia nigrescens*, *Ascophyllum nodosum*, *Laminaria japonica*, *Durvillea antartica*, *Durvillea potatorum* and, especially, *Laminaria hyperborea*.

10

Alginic acid is a linear hetero-polysaccharide comprising units of β -D-mannuronic acid and α -L-guluronic acid. Alginic acid may comprise homopolymeric sequences of mannuronic acid, homopolymeric sequences of guluronic acid, and mixed sequences of mannuronic acid and guluronic acid units. Use of alginic acid itself is contemplated in the present invention.

Salts of alginic acid used in the method of the present invention may include alkali metal salts, for example sodium and potassium salts, and ammonium and alkanolamine salts. Alkali metal salts are of particular interest.

The term "algins" as used herein includes alginic acid and salts of alginic acid, irrespective of the relative proportion of mannuronic and guluronic units, and is intended to include glycolated or alkoxylated derivatives, especially those derivatised with propylene glycol. However, preferred compounds are not alkoxylated or glycolated. Guluronic acid-rich alginic acid and guluronic acid-rich salts of alginic acid are of particular interest. Preferred compounds have at least

30

50%, more preferably 55-99%, most preferably 60-80% of guluronic units (by weight), the balance being mannuronic units. For guidance on production of algin very high in guluronic units the reader is referred to WO 98/51710.

5


The polymeric bodies may, if not inherently sequestrant, be processed in any of a number of ways. Sequestrant side chains may be grafted onto the bodies, for example using the well-known techniques of radiation
10 grafting or chemical grafting. Radiation grafting is described in WO 94/12545. Chemical grafting is described in GB 2086954A. Alternatively for certain side chains the polymeric bodies may be fabricated (for example melt spun) already bearing the sequestrant side-chains, as described
15 in EP 486934A. In yet other embodiments polymeric bodies not bearing sequestrant side chains may be coated with material which has the side chains. The polymeric bodies may, in effect, be regarded as carrying the side chains by mechanical adhesion. Alternatively they may attach by
20 cross-linking, as described in EP 992283A.

Preferably sequestrant side chains are any side-chains which can be carried by polymeric bodies, and which are able to bind calcium (and preferably other) ions, and
25 whose effectiveness in doing that is not substantially diminished by a cleaning agent. Suitable calcium-binding side-chains include residues of acids, for example of acrylic or methacrylic acid, or carboxylic acids, or of sulphonic acids, or of phosphonic acids. Residues of
30 organic acids are preferred. Particularly preferred are residues of methacrylic or, especially, acrylic acid.

Alternative calcium-binding side chains of polymeric bodies may include amino groups, quaternary ammonium salt groups and iminodicarboxyl groups $-N\{(CH_2)_nCOOH\}_2$, where n is 1 or 2.

5

Further suitable calcium-binding side chains of polymeric bodies may include acyl groups as described in EP 984095A. These have the formula




where X represents a residue in which one carboxyl group is eliminated from a monocarboxylic acid or dicarboxylic acid;

15


V represents hydrogen or a carboxyl group;

M represents hydrogen; or



25

wherein R^1 represents a residue in which one hydrogen is eliminated from a carbon chain in an alkylene group, R^2 represents a direct bond or an alkylene group, Y^1 and Y^2 are the same or different and each represents hydrogen, a
 30 carboxyl group, an amino group, a hydroxy group or a thiol group, n is an integer of 1 to 4, M' represents hydrogen or



5 wherein R^3 represents a residue in which one hydrogen is eliminated from a carbon chain in an alkylene group; R^4 represents a direct bond or an alkylene group, Y^3 and Y^4 are the same or different and each represents hydrogen, a carboxyl group, an amino group, a hydroxy group or a thiol
10 group; and Z represents hydrogen or has the same meaning as that of M.

Such side chains are preferably carried by polymeric fibres selected from polyolefins, poly(haloolefins),
15 poly(vinylalcohol), polyesters, polyamides, polyacrylics, protein fibres and cellulosic fibres (for example cotton, viscose and rayon). Polyolefins are especially preferred, particularly polyethylene and polypropylene.

20 When side chains are grafted onto the base polymeric bodies a preferred process is one using irradiation, in an inert atmosphere, with immediate delivery to irradiated bodies of acrylic acid. Preferably the radiation is electron beam or gamma radiation, to a total dose of 10-
25 300 kGy, preferably 20-100 kGy. The acrylic acid is preferably of concentration 20-80 vol %, in water, and the temperature at which the acrylic acid is supplied to the irradiated polymeric bodies is preferably an elevated temperature, for example 30-80°C. Preferably the base
30 polymeric bodies are polyethylene, polypropylene or cellulosic fibres.

In principle, however, any type of insoluble, calcium-binding material can be used.

Preferably the calcium-binding modifying agent is also
5 able to bind magnesium ions.

Preferably the calcium-binding modifying agent is substantially without means to capture anionic species in the water.

10

Preferably the container, including modifying agent(s) therein, is substantially without means to capture anionic species in the water.

15 The method of the invention is suitably carried out at a temperature in the range 5 to 100°C, especially 10 to 60°C, most preferably 20 to 60°C.

Preferably the container is able to move freely within
20 the water used in the method. Preferably the container is immersed in the water substantially throughout the method. Thus, it is preferably not in the form of a filter or like body, retained in a fixed orientation, or mounted on a frame (except in the third aspect of the invention,
25 defined hereinafter).

In the method of the invention the container could be a rigid body with microporous openings present throughout its enclosing wall (which term we use to denote a
30 container with one or several facets). It may be spherical or ovoid or cubic or cuboid, or any other convenient shape. It could comprise a rigid body, not necessarily with microporous openings throughout its wall,

but having one or more windows of a microporous material, set into its wall. Preferably it is a bag (by which we include a sachet or pouch), having a perforate outer wall, for example of a woven, knitted or preferably non-woven material, of textile or paper. Preferably the wall of a bag comprises sheets of material, each sheet comprising a ply of two or more layers. Thus, should any insoluble modifying agent inside the bag happen to pass through a perforation in one layer it will be presented with at least a second layer. Preferably the wall comprises a sheet with a ply of three or more layers, such that any insoluble modifying agent inside the bag must follow a tortuous pathway if it were to exit the bag through the wall.

15

The wall of a bag may conveniently consist of two sheets secured together about their periphery, with the modifying agent therebetween. The modifying agent could comprise a further sheet or sheets. The securement may be by means of adhesive or, preferably, heat sealing. When the securement is by heat sealing the sheets may comprise a thermoplastic to facilitate this. Conventional materials used in tea bag manufacture may be suitable, and the techniques used in making tea bags can be applied to make flexible containers useful in this invention. Such techniques are described in WO 98/36128 and EP 380127A.

The container could be discarded after use, or it could be regenerated, for example using sodium chloride to effect ion exchange, and re-used. A dye could be employed to give a colour change, on exhaustion of the modifying agent inside the container.

The modifying agent within the container could comprise a catalytic material, for example able to degrade soils and/or microorganisms.

5 Of course, a container may contain more than one type of modifying agent, and/or a modifying agent having a dual function, for example to capture calcium ions and release a beneficial species.

10 In addition to a substantially insoluble modifying agent the container could contain a soluble solid material or a dispersible solid material which can pass through the walls of the bag when immersed in water. Such a soluble or dispersible solid material could be, for example, any
15 of the materials mentioned above as being possible components of compositions with which the container can be used; but particularly includes a cleaning surfactant.

 Furthermore the wall of the container may itself act
20 as a further means for modifying the water, for example by having the capability of capturing undesired species in the water and/or releasing beneficial species. Thus, the wall material could be of a textile material with ion-capturing and/or ion-releasing properties, for example as
25 described above.

 In accordance with a second aspect of the invention there is provided a container having an enclosing wall and containing a substantially water-insoluble modifying agent
30 able to bind calcium ions, and a water-soluble or water-dispersible modifying agent comprising a cleaning surfactant, the wall being permeable to water and to the cleaning surfactant dissolved or dispersed therein but

impermeable to the substantially water-insoluble modifying agent.

In accordance with a third aspect of the invention
5 there is provided a method of providing improved cleaning
in a clothes washing machine, wherein a container
containing a substantially water-insoluble sequestrant
having a wall permeable to water and to metal ions therein
but impermeable to the sequestrant is located in the
10 loading drawer of the machine such that inflowing rinse
water flows through the container, thereby effecting the
softening of rinse water entering the machine.

Preferably water entering the machine and which is not
15 rinse water does not flow through the container.

The container used in the third aspect may be a rigid
body which is shaped to locate snugly in the tray such
that the inflowing rinse water is compelled to flow
20 through it. Alternatively it may be a flexible body, for
example a bag, which packs into the flow pathway for the
rinse water such that the rinse water is compelled to flow
through it. This is an efficient approach to softening
the water used in clothes washing machines. Suitably the
25 main wash water will not have flowed through the
container, but softening thereof is effected by the
conventional builders present in the laundry detergent
composition. Prior to rinsing, the wash water containing
the builders is drained away and only then is the rinse
30 water delivered into the machine, this rinse water having
been softened by flowing through the container located in
the loading tray. Neither the builders nor the
sequestrant in the container are active at the same time

as the other. Thus, they do not compete with each other and are not used wastefully.

In accordance with a fourth aspect of the invention
5 there is provided a container having a rigid enclosing wall and containing a substantially water-insoluble calcium ion sequestrant, the wall being permeable to water and to species dissolved therein but impermeable to the sequestrant, wherein the container is adapted to be
10 located in the loading drawer of a clothes washing machine such that inflowing rinse water flows through it. The sequestrant and the container having a rigid wall may be as described above. Preferably the rigid wall is adapted to be located in the loading drawer by mean of firmly
15 interengaging parts as between the container and the loading drawer, for example parts providing snap-fit securement and/or otherwise requiring mechanical force to separate them.

20 The invention will now be described, by way of example, with reference to the following embodiments.

Example 1

Use of acrylic acid grafted onto polyethylene fibres.

25

Chopped polyethylene fibres of 20 mm length were placed in a plastic bag, purged with nitrogen and sealed. The bag was irradiated with 10 MeV electrons from a linear accelerator. The total radiation dose was 30 kGy. The
30 fibres were removed from the bag and immersed without delay in a nitrogen-purged aqueous solution containing 40 vol % acrylic acid for 45 minutes at 62°C. The grafted fibres were extracted with water overnight. The grafted

fibres were placed between two sheets of non-woven polyethylene, which was heat sealed to enclose the grafted fibres. The bag was placed in the drum of a washing machine, with the clothes, at the start of a washing
5 cycle. It was removed, with the clothes, at the end of the cycle, having provided water softening throughout the cycle, to assist the washing process.

Example 2

10 Use of algin sequestrants

In this series of examples the use of algins retained in microporous containers, to soften hard water, was assessed.

15

1g of PROTANAL LF 20 was placed in between two 5 x 5 cm sheets of extruded polyester film SN 42 available from Smith & Nephew, York, UK, and which were heat sealed to enclose the algin.

20

PROTANAL LF 20 is a granular food grade sodium alginate available from FMC Biopolymer.

The pouch was placed in 1 litre of hard tap water (90 mg/l
25 Ca^{2+} approx.).

After 45 minutes most of the pale yellow coarse algin granules had hydrated and became gel-like. We concluded that calcium sequestration was taking place but that the
30 pouch was too small for the quantity of the algin.

Further tests were carried out using ordinary paper tea bag material, in the same hard tap water. Tea bags of

square flat form were carefully opened. The tea was discarded and the bags filled with 1 g of test material. The bags were re-sealed with adhesive. The bags were found in further tests to be highly effective.

5

The further tests were as follows:

Samples Control:	BRITA (Trade Mark) water filter ion exchange material, used to purify drinking water.
Alginate:	PROTANAL LF20
Alginic acid:	PROTACID F120

10

In each case 1 g of sample material was sealed in a bag made of tea bag paper, as described above.

15

Dosage:

1 litre hard water was treated with 1 g material in each case.

20

Water samples were filtered after treatment.

Sample test jars were rinsed with deionised water prior to sample storage.

25

Testing methods were as follows.

Controls

30 1.a. Hard water sample - untreated

Retain in 250 ml glass jar labelled: 1.a.

1.b. Hard water sample -filtered (Whatman No. 4 filter paper 15 cm)

Filter sample into jar.

Discard first 250 mls.

5 Retain second 250 mls in a jar labelled: 1.b.

1.c. Hard water sample - treated

1.c.i. PROTANAL LF20

10 Draw 1 litre tap water and leave on bench for temperature to reach 21°C.

Add 1 bag containing PROTANAL LF20 to the test water. Use magnetic stirrer.

Leave in contact for 10 minutes.

15 After 10 minutes contact remove bag.

Label a 250 ml glass jar.

Filter through Whatman No. 4 filter paper (15 cm) into jar.

Discard first 250 ml.

20 Retain next 250 mls for test in jar labelled 1.c.i.

1.c.ii. PROTACID 120

Repeat as for 1.c.i.

25 Store in jar labelled: 1.c.ii.

1.c.iii. BRITA ion exchange material

Repeat as for 1.c.i.

Store in jar labelled: 1.c.iii.

30

Effect of pH changes at 40°C on water treatment systems

The aim was to replicate the action in a clothes washing machine, on a smaller scale.

2.a. Hard water at pH 6 and 40°C

5 A total of 5 litres hard tap water was used.

2.a.i. Treated with PROTANAL LF20

10 Measure 2 litres hard tap water into a 5 litre beaker (equivalent to wash phase of a washing machine).

Allow temperature to reach 40°C.

Add 5 bags containing PROTANAL LF20.

Mix for 45 minutes using magnetic stirrer.

15 Remove bags, discard hot water and add bags to 1 litre of freshly drawn cold tap water (Rinse 1).

Do not heat.

Stir as detailed above for 10 minutes.

Filter 250 mls into a labelled glass jar through a Whatman No. 4 filter (label 2.a.i.1).

20 Discard and retain a second 250 mls in the jar.

Add the bags to a 1 litre freshly drawn water (Rinse 2).

Stir for 10 minutes. Do not heat.

25 After 10 minutes remove bags and add to a third litre of fresh tap water (Rinse 3).

Filter, discard first 250 ml and retain second 250 ml sample in jar labelled 2.a.i.2.

Stir the third sample for 10 minutes.

30 After 10 minutes filter, discard, filter and retain second 250 mls, as before.

Store in a jar labelled 2.a.i.3.

2.a.ii. Treated with PROTACID F120

Repeat the test procedure detailed in 2.a.i. using 5 bags containing alginic acid.

Store samples from the three "rinse" cycles in jars labelled:

5 2.a.ii.1, 2.a.ii.2 and 2.a.ii.3.

2.a.iii. Treated with BRITA ion exchange material

10 Repeat test procedure detailed in 2.a.i. using 5 bags containing the BRITA material.

Store samples from the three "rinse" cycles in jars labelled:

2.a.iii.1, 2.a.iii.2 and 2.a.iii.3.

15 **2.b. Hard water at pH 9 and 40°C**

2.b.i. Treated with PROTANAL LF20

Measure 2 litres of hard tap water into a 5 litre beaker.

20 Add the same large magnetic stirrer as used in 2.a and maintain a good stir.

Add sufficient 1M sodium hydroxide dropwise, using a plastic pipette, to raise the pH to 9.

Raise the temperature to 40°C with constant stirring.

25 When this temperature is reached add 5 bags containing PROTANAL LF20.

Repeat procedure detailed in 2.a.i. after "Mix for 45 minutes using magnetic stirrer".

30 Store the samples from the three rinse cycles in jars labelled:

2.b.i.1, 2.b.i.2 and 2.b.i.3.

2.b.ii Treated with PROTACID F120

Measure 2 litres hard tap water into a 5 litre beaker.
Add the large magnetic stirrer as used in 2.a and
maintain a good stir.

5 Add sufficient 1M sodium hydroxide dropwise from a
plastic pipette to raise the pH to 9.

Raise the temperature to 40°C with constant stirring.
When this temperature is reached add 5 bags
containing PROTANAL F120 .

10 Repeat procedure detailed in 2.a.i. after "Mix for 45
minutes using magnetic stirrer".

Store the samples from the three rinse cycles in jars
labelled:

2.b.ii.1, 2.b.ii.2 and 2.b.ii.3.

15 **2.b.iii Treated with BRITA ion exchange
material**

Repeat the above procedure with 5 bags containing the
BRITA ion exchange material.

20 Store samples from the three "rinse" cycles in jars
labelled:

2.b.iii.1, 2.b.iii.2 and 2.b.iii.3.

Effect of high pH and high temperature on water treatment
systems

25

3.a. Treated with PROTANAL LF20

Measure 2 litres of hard tap water into a 5 litre
beaker and add the large magnetic stirrer.

Set to a good stir.

30 Adjust the pH to pH 11 by adding 1M sodium hydroxide
dropwise using a plastic pipette.

Raise temperature to 60°C.

Add 5 bags containing PROTANAL LF20.

Leave for 90 minutes.

Remove the bags and place in 1 litre cold tap water, with a magnetic stirrer.

Repeat the test procedure as detailed in 2.a.i after

5 "Do not heat".

Store the samples from three "rinses" in jars labelled:

3.a.i, 3.a.ii and 3.a.iii.

10 **3.b. Treated with PROTACID F120**

Repeat the procedure in 3.a. using 5 bags of PROTACID F120.

Store the samples from three "rinses" in jars labelled:

15 3.b.i, 3.b.ii and 3.b.iii.

3.c. Treated with BRITA ion exchange material

Repeat the procedure in 3.b. using 5 bags of BRITA ion exchange material.

20 Store the samples from three "rinses" in jars labelled:

3.c.i, 3.c.ii and 3.c.iii.

Calcium ion concentrations were measured by Atomic
25 Absorption Spectroscopy (AAS) using a Perkin Elmer Atomic Absorption Spectrometer Model 3300 with Windows Software; and by Inductively Coupled Plasma - Atomic Emission Spectroscopy (ICPAES), using a Perkin Elmer Plasma 40 emission ICP instrument. Both AAS and ICPAES are
30 comparative techniques for which calibration curves have to be set up.

In addition an Orion 710 Calcium Ion Selective Electrode was used to measure calcium ion concentration.

The results are shown in Tables 1, 2 and 3 below. The
5 calcium concentrations measured vary according to the test
employed. The effect of the sequestrant on the test
methods is not known. However certain trends may clearly
be seen, for example the high level of effectiveness of
PROTACID F120 across a wide pH range.

10

Copper ion levels were also measured by the ICPAES
technique and the results are shown in Table 4 below.
Again, the trend suggests that the algins, especially
PROTACID F120, can significantly reduce copper ion
15 concentrations.

Table 1 AAS results

	Conditions	Treatment	Ref No	CALCIUM ion conc, PPM		
				[Conc]	[Change]	% reduction
Control *	Hard Tap Water Ambient temp	None	1.a	88.7		
	Hard Tap Water Ambient temp	Filtered thro Whatman No 4	1.b	87.5		
Unadjusted	Temp = 21°C Contact time 10 mins Stirred & filtered	PROTANAL LF20	1.c.i	91.9	4.4	
	As above	PROTACID F120	1.c.ii	36.9	-50.6	57.8%
	As above	BRITA	1.c.iii	90.6	2.9	
pH 6 @ 40°C	Initial 45 min @ 40°C & pH 6. Followed by 3x 10 min tap water rinses. All rinses filtered.	PROTANAL LF20				
		Rinse 1	2.a.i.1	91.2	3.7	
		Rinse 2	2.a.i.2	90.6	3.1	
	As above	Rinse 3	2.a.i.3	90.0	2.5	
		PROTACID F120				
		Rinse 1	2.a.ii.1	53.1	-34.4	39.3%
		Rinse 2	2.a.ii.2	77.5	-10.0	11.4%
		Rinse 3	2.a.ii.3	74.4	-13.1	15.0%
	As above	BRITA				
		Rinse 1	2.a.iii.1	80.6	-6.9	7.8%
		Rinse 2	2.a.iii.2	88.1	0.6	
		Rinse 3	2.a.iii.3	88.1	0.6	
pH 9 @ 40°C	Initial 45 mins @ 40°C & pH 9 followed by 3 x 10 min tap water rinses. All rinses filtered.	PROTANAL LF20				
		Rinse 1	2.b.i.1	88.1	0.6	
		Rinse 2	2.b.i.2	86.6	-0.9	1.0%
	As above	Rinse 3	2.b.i.3	82.5	-5.0	
		PROTACID F120				
		Rinse 1	2.b.ii.1	65.6	-21.9	25.0%
		Rinse 2	2.b.ii.2	69.4	-18.1	20.7%
		Rinse 3	2.b.ii.3	31.2	-56.2	64.3%
	As above	BRITA				
		Rinse 1	2.b.iii.1	83.1	-4.4	5.0%
		Rinse 2	2.b.iii.2	86.2	-1.2	1.4%
		Rinse 3	2.b.iii.3	86.9	-0.6	0.7%
pH 9 @ 60°C	Initial 90 mins @ 60°C & pH 11 followed by 3 x 10 min tap water rinses. All rinses filtered.	PROTANAL LF20				
		Rinse 1	3.a.i	87.5	0.00	
		Rinse 2	3.a.ii	86.9	-0.6	0.7%
	As above	Rinse 3	3.a.iii	86.5	-1.0	
		PROTACID F120				
		Rinse 1	3.b.i	86.5	-1.0	1.1%
		Rinse 2	3.b.ii	86.5	-1.0	1.14
		Rinse 3	3.b.iii	83.1	-4.4	5.0%
	As above	BRITA				
		Rinse 1	3.c.i	64.4	-23.1	26.4%
		Rinse 2	3.c.ii	76.9	-10.6	12.1%
		Rinse 3	3.c.iii	81.2	-6.2	7.1%

* All changes in ion concentrations calculated from this constant.

Table 2 ICPAES results on calcium

	Conditions	Treatment	Ref No	CALCIUM ion conc (PPM)		
				Conc]	[Change]	% reduction
Controls *	Hard Tap Water Ambient Temp	None	1.a	129.1		
	Hard Tap Water Ambient Temp	Filtered thro Whatman No 4	1.b	132.4		
Unadjusted	Temp = 21°C	PROTANAL LF20	1.c.i	120.8	-11.6	8.8%
pH 6 @ 40°C	Contact time 10 mins Stirred & filtered As for 1.c.i	PROTACID 120	1.c.ii	83.5	-48.9	36.9%
	As for 1.c.i	BRITA	1.c.iii	132.8	0.4	
	Initial 45 min @ 40°C & pH 6. Followed by	PROTANAL LF20	2.a.i.1	129.2	-3.2	2.4%
	3x 10 min tap water rinses. All rinses filtered	Rinse 1	2.a.i.2	125.9	-6.5	4.9%
		Rinse 2	2.a.i.3	132.2	-0.2	0.1%
		Rinse 3				
	As above	PROTACID F120				
		Rinse 1	2.a.ii.1	113.3	-19.1	14.4%
		Rinse 2	2.a.ii.2	129.2	-3.2	2.4%
		Rinse 3	2.a.ii.3	111.3	-21.1	16.0%
	As above	BRITA				
		Rinse 1	2.a.iii.1	121.6	-10.8	8.1%
pH 9@ 40°C		Rinse 2	2.a.iii.2	128.1	-4.3	3.2%
		Rinse 3	2.a.iii.3	128.8	-3.6	2.7%
	Initial 45 mins @ 40°C & pH 9 followed by 3 x 10 min tap water rinses. All rinses filtered.	PROTANAL LF20	2.b.i.1	128.7	-3.4	2.5%
	As above	Rinse 1	2.b.i.2	130.5	-1.9	1.4%
		Rinse 2	2.b.i.3	126.4	-6.0	4.5%
		Rinse 3				
		PROTACID F120				
		Rinse 1	2.b.ii.1	46.6	-85.7	64.8%
		Rinse 2	2.b.ii.2	114.4	-18.0	13.6%
		Rinse 3	2.b.ii.3	138.4	6.0	
	As above	BRITA				
		Rinse 1	2.b.iii.1	119.4	-13.0	9.8%
pH 9 @ 60°C		Rinse 2	2.b.iii.2	120.5	-11.9	8.9%
		Rinse 3	2.b.iii.3	126.7	-5.7	4.3%
	pH 9 followed by 3 x 10 min tap water rinses. All rinses filtered.	PROTANAL LF20	3.a.i	121.9	-10.5	7.9%
		Rinse 1	3.a.ii	131.5	-0.9	0.6%
		Rinse 2	3.a.iii	127.1	-5.3	4.0%
		Rinse 3				
	As above	PROTACID 120				
		Rinse 1	3.b.i	116.9	-15.5	11.7%
		Rinse 2	3.b.ii	129.2	-3.2	2.4%
		Rinse 3	3.b.iii	125.8	-6.6	4.9%
	As above	BRITA				
		Rinse 1	3.c.i	95.0	-37.4	28.2%
		Rinse 2	3.c.ii	121.4	-11.0	8.3%
		Rinse 3	3.c.iii	130.2	-2.2	1.6%

* all changes in ion concentration calculated from this constant

Table 3 - Calcium electrode results

	Conditions	Treatment	Ref No	(Conc)	CALCIUM Ion Concentration in ppm (change) % reduction	
Controls *	Hard Tap Water Ambient temp	None	1.a	232.0		
	Hard Tap Water Ambient temp	Filtered thro Whatman No 4	1.b	235.0		
Unadjusted	Temp 21°C Contact time 10 mins Stirred & filtered	PROTANAL LF20	1.c.i	225.0	-10.0	4.2%
	As above	PROTACID F120	1.c.ii	67.1	-167.9	71.4%
	As above	BRITA	1.c.iii	211.0	-24.0	10.2%
pH 6 @ 40°C	Initial 45 min @ 40°C & pH 6. Followed by 3x 10 min tap water rinses. All rinses filtered.	PROTANAL LF20				
		Rinse 1	2.a.i.1	178.0	-57.0	24.2%
		Rinse 2	2.a.i.2	184.0	-51.0	21.7%
		Rinse 3	2.a.i.3	173.0	-62.0	26.4%
	As above	PROTACID 120				
		Rinse 1	2.a.ii.1	115.0	-120.0	51.1%
		Rinse 2	2.a.ii.2	167.0	-68.0	28.9%
		Rinse 3	2.a.ii.3	167.0	-68.0	28.9%
	As above	BRITA				
		Rinse 1	2.a.iii.1	169.0	-66.0	28.1%
		Rinse 2	2.a.iii.2	189.0	-46.0	19.6%
		Rinse 3	2.a.iii.3	199.0	-36.0	15.3%
pH 9 @ 40°C	Initial 45 mins @ 40°C & pH 9 followed by 3 x 10 min tap water rinses. All rinses filtered.	PROTANAL LF20		1b reading = 179 mg/l		
		Rinse 1	2.a.i.1	219.0	57.0	
		Rinse 2	2.b.i.2	201.0	39.0	
		Rinse 3	2.b.i.3	192.0	30.0	
	As above	PROTACID F120				
		Rinse 1	2.b.ii.1	147.0	-15.0	9.2%
		Rinse 2	2.b.ii.2	145.0	-17.0	10.5%
		Rinse 3	2.b.ii.3	54.4	-107.6	66.4%
	As above	BRITA				
		Rinse 1	2.b.iii.1	204.0	42.0	
		Rinse 2	2.b.iii.2	204.0	42.0	
		Rinse 3	2.b.iii.3	198.0	36.0	
PH 9 @ 60°C	Initial 90 mins @ 60°C & pH 9 followed by 3 x 10 min tap water rinses. All rinses filtered	PROTANAL LF20				
		Rinse 1	3.a.i	207.0	45.0	
		Rinse 2	3.a.ii	198.0	36.0	
		Rinse 3	3.a.iii	207.0	45.0	
	As above	PROTACID 120				
		Rinse 1	3.b.i	195.0	33.0	
		Rinse 2	3.b.ii	182.0	20.0	
		Rinse 3	3.b.iii	183.0	21.0	
	As above	BRITA				
		Rinse 1	3.c.i	110.0	-52.0	32.1%
		Rinse 2	3.c.ii	135.0	-27.0	16.7%
		Rinse 3	3.c.iii	141.0	-21.0	13.09%

* All changes in ion concentrations calculated from this constant.

Table 4 ICPAES results on copper

	Conditions	Treatment	Ref No	COPPER [Conc]	[Change]	% reduction
Controls *	Hard Tap Water Ambient Temp	None	1.a	0.079		
	Hard Tap Water Ambient Temp	Filtered thro Whatman No 4	1.b	0.163		
Unadjusted	Temp = 21°C	PROTANAL LF20	1.c.i	1.317	1.154	
pH 6 @ 40°C	Contact time 10 mins Stirred & filtered As for 1.c.i	PROTACID 120	1.c.ii	0.071	-0.092	56.4%
	As for 1.c.i	BRITA	1.c.iii	0.244	0.081	
	Initial 45 min @ 40°C & pH 6. Followed by 3x 10 min tap water rinses. All rinses filtered	PROTANAL LF20	2.a.i.1	0.798	0.635	
		Rinse 1	2.a.i.2	0.238	0.675	
		Rinse 2	2.a.i.3	0.329	0.166	
		Rinse 3				
	As above	PROTACID F120				
		Rinse 1	2.a.ii.1	0.194	0.031	
		Rinse 2	2.a.ii.2	0.307	0.144	
		Rinse 3	2.a.ii.3	0.173	0.010	
	As above	BRITA				
		Rinse 1	2.a.iii.1	0.301	0.138	
pH 9@ 40°C	Initial 45 mins @ 40°C & pH 9 followed by 3 x 10 min tap water rinses. All rinses filtered. As above	PROTANAL LF20	2.b.i.1	0.232	0.069	
		Rinse 1	2.b.i.2	0.140	-0.023	14.1%
		Rinse 2	2.b.i.3	0.311	0.148	
		Rinse 3				
	As above	PROTACID F120				
		Rinse 1	2.b.ii.1	0.055	-0.108	66.2%
		Rinse 2	2.b.ii.2	0.126	-0.037	22.7%
		Rinse 3	2.b.ii.3	0.390	0.227	
	As above	BRITA				
		Rinse 1	2.b.iii.1	1.801	1.638	
		Rinse 2	2.b.iii.2	0.462	0.299	
		Rinse 3	2.b.iii.3	0.268	1.5	
pH 9 @ 60°C	pH 9, followed by 3 x 10 min tap water rinses. All rinses filtered.	PROTANAL LF20	3.a.i	0.300	0.137	
		Rinse 1	3.a.ii	0.325	0.162	
		Rinse 2	3.a.iii	0.166	0.003	
		Rinse 3				
	As above	PROTACID 120				
		Rinse 1	3.b.i	0.171	0.008	
		Rinse 2	3.b.ii	0.159	-0.004	
		Rinse 3	3.b.iii	0.323	0.167	2.4%
	As above	BRITA				
		Rinse 1	3.c.i	0.232	0.069	
		Rinse 2	3.c.ii	0.192	0.029	
		Rinse 3	3.c.iii	0.231	0.068	

* all changes in ion concentration calculated from this constant

A further test was carried out to assess effectiveness at pH 10.5, the typical pH of the washing medium in part of a washing machine cycle.

5

If the pH of the same hard water is raised to 10.5 by the addition of 1M sodium hydroxide dropwise, the solution becomes cloudy at pH 10.5 and a precipitate of insoluble calcium hydroxide falls to the bottom of the container on
10 standing.

1 g samples of sequestrants, contained in bags made as described above from tea bag material, were added to 800g of the same hard tap water, stirred for 2 minutes and then
15 the pH of the solution increased to pH 10.5 by the addition of 1M sodium hydroxide, dropwise. The solution was stirred throughout the test to ensure thorough mixing. Any cloudiness or precipitate was noted.

20 The test was repeated with increasing amounts of sequestrant until no cloudiness or precipitate was seen at pH 10.5. We concluded that sufficient sequestrant had been added initially to react with all the dissolved calcium, leaving none free to precipitate at pH 10.5.

25

Results

Sequestrant	Mass of sequestrant required to react with all dissolved calcium
30 1. PROTACID F120	1 g
2. PROTANAL LF20	4 g
3. BRITA ion exchange	4 g

Example 3Use of algin suquestrant with different bag materials

In further experiments alternative bag materials were
5 explored, namely J R Crompton's polypropylene-faced
cellulose papers identified below and SciMAT's
polypropylene paper. Information on these is as follows.

Make	Ref No	Grammage (gsm)	Air Permeab. m ³ /min/m ²	Wet burst strength
JR Crompton	474604	21.0	50	22 kPa
JR Crompton	474608	27.5	36	32 kPa
SciMAT	700/9	45-45		

10

The bags were made by heat sealing together 7 cm x 7 cm
sheets of the papers, with PROTACID F120 (1g) between
them. The filled bags were placed in containers containing
15 the same hard water (1 litre) and stirred for 30 minutes.
The water was then observed by eye, and the condition
recorded, as noted in the following table.

Material	Duration of stirring	Observations after 30 minutes
474608	30 mins	Water remained clear
474604	30 mins	Slight cloudiness
SciMAT	30 mins	Slight leakage/cloudiness

20

Example 4Use of functionalised viscose in bag

In further experiments J.R. Crompton's SUPERSEAL (trade mark) three-ply tea bag paper, ref no. 478404, grammage 26.0 gsm, was used to retain radiation grafted viscose fibres. The chopped viscose fibres had been
5 irradiated under a nitrogen atmosphere using an electron-beam accelerator. Once the dosage had reached a specified value in kGy the fibres had been immersed immediately in a nitrogen-purged aqueous solution of acrylic acid, at a moderately elevated temperature.

10

A first bag, 7 cm x 7 cm, contained 0.884g of functionalised fibres (19% dry weight) and reduced the calcium ion concentration of a hard water from 174.3 ppm to 132.3 ppm. A second bag, 7 cm x 7 cm, contained 1.768g
15 of functionalised fibres and reduced the calcium ion concentration of a hard water from 168.3 ppm to 92.3 ppm, (both measured by EDTA titration)

Example 5

20 Use of laminated radiation grafted cloth in container

A heat sealed laminate comprised a middle calcium sequestrant layer between two outer layers, the latter forming a container for the sequestrant layer.

25

Composition of each outer layer:

20g/m² sheet weight, laid (non-woven) fibres, a blend of:

30 20% cellulose, 10 mm staple length

40% viscose, 10 mm staple length

20% polyester bicomponent, 6mm staple length

20% polyester bicomponent, 12mm staple length

Composition of middle layer:

75g/m² sheet weight, laid (non-woven) fibres, a blend of:

5

80% 10 mm staple length viscose fibres radiation grafted
with 7.5mM/g carboxylate functionality

10% polyester bicomponent, 6mm staple length

10% polyester bicomponent, 12mm staple length

10

A 4.5cm x 4.5cm piece of this container immersed for
30 minutes in 500ml hard water, at 60°C, reduced the
calcium ion level from 170mg/l to 143mg/l (determined by
EDTA titration).

15

Example 6

Use of polyacrylate cloth in container

Polyacrylate fibres are made by copolymerising acrylic
20 acid, sodium acrylate, methacrylic acid and
hydroxypropylmethacrylic acid in an aqueous premix.
Polymerisation is initiated by ammonium persulphate. The
resulting cross-linked polymer is extruded into a hot air
stream into fibres. These fibres are then incorporated
25 with other fibres into a non-woven cloth. In this example
the cloth was 145g/m² sheet weight, of:

50%wt polyacrylate fibre, described above

50%wt polyester bicomponent

30

This non-woven cloth was retained within a layer of
30g/m² spunbonded polypropylene laminated onto both sides
to give a three layer flat-form container.

A 4.5cm x 4.5cm piece of this container immersed for 30 minutes in 500ml hard water, at 60°C, reduced the calcium level from 170mg/l to 148mg/l (determined by EDTA
5 titration).

Example 7

Machine wash tests

10 The containers described in Examples 5 and 6 were used in washing machine testing in order to assess calcium carbonate encrustation on the heating element. The washing machine employed was a CANDY 80 PLUS (trade mark). Each washing load was 3.5 kg. A 60°C programme was
15 selected. The water hardness was 172 mg/l Ca^{2+} . The detergent employed was 168g DASH ESSENTIAL (trade mark), a commercial washing powder available in supermarkets in Italy, having the following composition (by weight):

20	anionic surfactant	11.7%
	zeolite	18.9%
	sodium silicate	2.7%
	sodium citrate	3.5%
	sodium carbonate	25.9%
25	sodium percarbonate	11.5%
	TAED	1.4%
	Protease	0.2%
	Amylase	0.8%
	Phosphonate	0.3%
30	Polymer	1.6%

Prior to the experiments the washing machine element was weighed. It was re-weighed after 15 washes. The results were as follows:

5	Detergent alone	660mg HEE
	Detergent + Ex.5 tri-ply container	560mg HEE
	Detergent + Ex.6 tri-ply container	450mg HEE

HEE = Heating Element Encrustation

10

All containers were approximately 625cm² in area and a fresh container was used for each wash cycle.

CLAIMS

1. A method of cleaning household articles wherein
cleaning water is contacted with a container having an
5 enclosing wall and containing a substantially water-
insoluble modifying agent able to bind calcium ions, the
wall being permeable to the water and to components
dissolved therein but retaining the substantially water-
insoluble modifying agent.
- 10 2. A method as claimed in claim 1, being a ware washing
method using a ware washing machine.
3. A method as claimed in claim 2, wherein the machine is
15 a clothes washing machine.
4. A method as claimed in claim 1, wherein the method is
a manual cleaning method.
- 20 5. A method as claimed in any preceding claim, wherein
the container is a bag.
6. A method as claimed in any preceding claim, wherein
the substantially water-insoluble modifying agent is an
25 algin.
7. A method as claimed in any of claims 1 to 5, wherein
the substantially water-insoluble modifying agent is an
ion exchange resin.
- 30 8. A method as claimed in any preceding claim, wherein
the container wall itself also changes the properties of
the water.

9. A method as claimed in any preceding claim, wherein the container additionally contains a water-soluble or water-dispersible modifying agent able to change the properties of the water.

10. A method as claimed in claim 9 wherein the water-soluble or water-dispersible modifying agent comprises a cleaning surfactant.

10

11. A container having an enclosing wall and containing a substantially water-insoluble modifying agent able to bind calcium ions, and a water-soluble or water-dispersible modifying agent comprising a cleaning surfactant, the wall being permeable to water and to the cleaning surfactant dissolved or dispersed therein but impermeable to the substantially water-insoluble modifying agent.

12. A method of providing improved cleaning in a clothes washing machine, wherein a container containing a substantially water-insoluble sequestrant having a wall permeable to water and to metal ions therein but impermeable to the sequestrant is located in the loading drawer of the machine such that inflowing rinse water flows through the container, thereby effecting the softening of rinse water entering the machine.

13. A container having a rigid enclosing wall and containing a substantially water-insoluble calcium ion sequestrant, the wall being permeable to water and to species dissolved therein but impermeable to the sequestrant, wherein the container is adapted to be

located in the loading drawer of a clothes washing machine such that inflowing rinse water flows through it.

14. A method of cleaning household articles substantially
5 as hereinbefore described with particular reference to the examples.

15. A container substantially as hereinbefore described with particular reference to the examples.

PCT/GB 01/03927

A. CLASSIFICATION OF SUBJECT MATTER
IPC 7 C02F5/10 C11D17/00

According to International Patent Classification (IPC) or to both national classification and IPC

B. FIELDS SEARCHED

Minimum documentation searched (classification system followed by classification symbols)
IPC 7 C02F C11D

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

Electronic data base consulted during the international search (name of data base and, where practical, search terms used)

EPO-Internal, PAJ, WPI Data

C. DOCUMENTS CONSIDERED TO BE RELEVANT

Category *	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
P, X	WO 01 21536 A (CORNELIUS GAY JOYCE ; JOLLIFFE IAN GORDON (GB); MCKECHNIE MALCOLM T) 29 March 2001 (2001-03-29) page 1, line 4 -page 9, line 20 ---	1-15
X	EP 0 279 471 A (PROCTER & GAMBLE) 24 August 1988 (1988-08-24) ---	1-3, 5, 8-11, 13-15
A	page 4, line 36 -page 7, line 14 ---	4, 6, 7, 12
X	EP 0 011 501 A (UNILEVER NV ; UNILEVER LTD (GB)) 28 May 1980 (1980-05-28) page 2, line 21 -page 8, line 37 ---	1-5, 10, 11, 14, 15
A	US 4 348 293 A (TUNE JOHN B ET AL) 7 September 1982 (1982-09-07) claims 1-17 ---	1-15
	--- -/-	

☒ Further documents are listed in the continuation of box C.

☒ Patent family members are listed in annex.

* Special categories of cited documents :

A document defining the general state of the art which is not considered to be of particular relevance

E earlier document but published on or after the international filing date

L document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)

O document referring to an oral disclosure, use, exhibition or other means

P document published prior to the international filing date but later than the priority date claimed

T later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention

X document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone

Y document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art.

Z document member of the same patent family

Date of the actual completion of the international search

14 December 2001

Date of mailing of the international search report

21/12/2001

Name and mailing address of the ISA

European Patent Office, P.B. 5818 Patentlaan 2
NL - 2280 HV Rijswijk
Tel. (+31-70) 340-2040, Tx. 31 651 epo nl,
Fax: (+31-70) 340-3016

Authorized officer

Assogna, R

C.(Continuation) DOCUMENTS CONSIDERED TO BE RELEVANT

Category *	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
A	US 4 659 496 A (FOOTE MICHAEL R ET AL) 21 April 1987 (1987-04-21) column 3, line 9 -column 11, line 34 -----	1-15
A	PATENT ABSTRACTS OF JAPAN vol. 010, no. 172 (C-354), 18 June 1986 (1986-06-18) & JP 61 021781 A (NIPPON NOYAKU KK), 30 January 1986 (1986-01-30) abstract -----	

Patent document cited in search report		Publication date	Patent family member(s)	Publication date
WO 0121536	A	29-03-2001	AU 7434200 A	24-04-2001
			WO 0121536 A1	29-03-2001
			GB 2356202 A	16-05-2001
EP 0279471	A	24-08-1988	US 4733774 A	29-03-1988
			AT 80654 T	15-10-1992
			CA 1318212 A1	25-05-1993
			DE 3874562 D1	22-10-1992
			DE 3874562 T2	18-02-1993
			EP 0279471 A2	24-08-1988
			ES 2034150 T3	01-04-1993
EP 0011501	A	28-05-1980	AU 5292279 A	22-05-1980
			BR 7908915 A	21-07-1981
			EP 0011501 A1	28-05-1980
			ES 486069 D0	16-12-1980
			ES 8101641 A1	16-03-1981
			WO 8001077 A1	29-05-1980
			JP 55500901 T	06-11-1980
			ZA 7906190 A	24-06-1981
US 4348293	A	07-09-1982	AR 229571 A1	30-09-1983
			AU 534223 B2	12-01-1984
			AU 5292379 A	22-05-1980
			BR 7908913 A	21-07-1981
			CA 1130694 A1	31-08-1982
			EP 0011502 A1	28-05-1980
			ES 486067 D0	16-12-1980
			ES 8101639 A1	16-03-1981
			WO 8001078 A1	29-05-1980
			JP 60024838 B	14-06-1985
			JP 55500902 T	06-11-1980
			MX 151028 A	11-09-1984
			ZA 7906189 A	24-06-1981
US 4659496	A	21-04-1987	AU 6812087 A	06-08-1987
			CA 1258254 A1	08-08-1989
			EP 0233027 A2	19-08-1987
			JP 2514347 B2	10-07-1996
			JP 62246999 A	28-10-1987
			JP 2611160 B2	21-05-1997
			JP 8225799 A	03-09-1996
			NZ 219037 A	29-01-1990
			US RE33646 E	23-07-1991
JP 61021781	A	30-01-1986	NONE	

**This Page is Inserted by IFW Indexing and Scanning
Operations and is not part of the Official Record**

BEST AVAILABLE IMAGES

Defective images within this document are accurate representations of the original documents submitted by the applicant.

Defects in the images include but are not limited to the items checked:

- ☐ BLACK BORDERS
- ☐ IMAGE CUT OFF AT TOP, BOTTOM OR SIDES
- ☒ FADED TEXT OR DRAWING
- ☒ BLURRED OR ILLEGIBLE TEXT OR DRAWING
- ☐ SKEWED/SLANTED IMAGES
- ☐ COLOR OR BLACK AND WHITE PHOTOGRAPHS
- ☐ GRAY SCALE DOCUMENTS
- ☒ LINES OR MARKS ON ORIGINAL DOCUMENT
- ☒ REFERENCE(S) OR EXHIBIT(S) SUBMITTED ARE POOR QUALITY
- ☐ OTHER: _____

IMAGES ARE BEST AVAILABLE COPY.

As rescanning these documents will not correct the image problems checked, please do not report these problems to the IFW Image Problem Mailbox.